

**Roysons Terralon™ Contract****Wallcovering Specifications****Product Name:** Terralon™**Description:** PVC Free Eco-friendly Type II 54" Contract Wallcovering with 31% Post Consumer Recycled Content**Construction:** 100% Terralon™ (Proprietary Polyester/Natural Fiber Technology)**Weight:** 14oz PLY / 435.2 G/PLM 9.3oz PSY / 315.3 G/PSM**Physicals:** Meets or exceeds Federal Specification CCCW-408D for Type II Wallcoverings**Environmental:** PVC & POA (Olefin) Free, No Plasticizers, No Phthalates, No Formaldehyde, No Chlorine, No Halogens, No Heavy Metals, including: Cadmium, Mercury, Lead, or Zinc, and No Ozone Depleting Chemicals.

Minimum of 31% post-consumer recycled content

Recyclable\*

Breathable\*\* -very high permeability rating of 66 Perms based on ASTM E96 Procedure B (Wet Cup)

Made with 100% water based ink and adhesive systems

No harmful off gassing

Low Voc emitting

**Air Quality:** Meets California Section IAQ 1350– Third party certified by Berkeley Analytical Associates**Flame & Smoke:** Class "A" Fire Rated – tested in accordance with ASTM-E84 Tunnel Test  
NFPA-101 Life Safety Code**LEEDS Eligibility:** Terralon™ can contribute towards the earning of 2 LEEDs credits and, conditionally, 4 others-

MR Credit 4.1 Recycled content 10%

MR Credit 4.2 Recycled content 20%

NOTE: All LEED credits are based on the total construction of a building. Terralon™ offers up to a 50% advantage over competitive products for achieving MR Credit 4.1 and MR Credit 4.2 because of its higher percentage of post consumer recycled materials.

Conditionally-

MR Credit 2.1 Contribution to project recycling program

MR Credit 2.2 Contribution to project recycling program

MR Credit 5.1 Manufactured local to the new construction

EQ Credit 4.1 When mounted with use of low emitting adhesives

**Warranty:** 5 Year Warranty against manufacturing defects. Additional information regarding warranty is available on our website at <http://www.roysons.com/>**Comments:** \*All Terralon™ wallcoverings are recyclable. Construction waste and after use material can be returned to Roysons for recycling back into wallcovering and other industrial products as part of the Roysons Reclamation Program. For details visit <http://www.roysons.com/>

\*\*Permeable surface allows transfer of moisture to minimize possibility of mold and mildew growth. Terralon™ is intended for use in buildings that are properly designed and maintained to avoid moisture infiltration, condensation, and/or accumulation at wall cavities and wall surfaces, especially in warm, humid climates. ASTM E96 Procedure B (Wet Cup) performed by VARTEST company.